

Crate ESD RL-KLT 6280



KLT crates with a smooth sub-floor and waterdrainage holes in the can ideally be used for areas where liquids shall be drained off. Stable impact surfaces on the front and the sides allow the use in mini-load system; lifting slots the vertical retrieval and special holes the fixing of lid sealings. Perfectly usable for manual handling due to their ergonomic grips at the front walls and their practical support grips on the side walls.

Product code: 968091

Number of pieces on the pallet: 40



Technical specification

Features:	
Colour	black
Material	ESD
Volume	47 I
Weight	2.67 kg

Specification

Flow/surface resistance: 10⁴< 10¹⁰ Ohm

Please note that, due to the orientation of the flow derived from the processing method, finished components may exhibit different electrical properties in connection with electrostatic discharge (ESD).

All technical data of the products, including dimensions and weights, are subject to changes resulting from testing conditions and production technology. No legally binding guarantees of specific properties can be inferred from the information obtained.

We reserve all rights, including the right to unforeseen errors and subsequent modifications. We emphasize that the presented technical data is for informational purposes only and may be subject to changes without prior notice.

rs and ed e

info@tbaplast.cz

+ 420 565 534 000

Dimensions	
Length	60 cm
Widht	40 cm
Height	28 cm
Internal dimensions	
Internal dimension length	54.4 cm
Internal dimension width	35.9 cm
Internal dimension height	26.2 cm